

Daytek® Rotary Clothesline M38



Daytek Rotary Clotheslines have an adjustable drying height of 260mm and come with pre-strung and pre-tensioned lines ready for installation.

Each Daytek Rotary Clothesline includes a Ground Socket featuring 3 installation heights with 120mm of adjustment. The Rotary head can be folded down and the entire Clothesline can be easily

removed from the ground socket for storage when not in use giving back valuable yard space.

With a total of 38 metres of line space and a maximum outer line length of 2.2 metres the M38 Rotary can easily accommodate double size flat sheets.

Custom colours are available through the Special Orders desk.

Standard Colours

Hawthorn Green	A02841005	0137960
Anthracite Black	A02843001	0137961

Related Products

Ground Socket
Replacement Clothesline Cord (Hank)
Gentle Grip Pegs
Sock Holder

Features & Benefits

High tensile steel tube for maximum strength
Galvanised and powder coated for corrosion resistance
6 Lines; 38 metres of hanging space
Pre-strung lines with tensioning blocks for line rigidity
Coat hanger rings at the end of each arm
Ground Socket with 3 height adjustments included
Push button easy release central hub allows you to fold away the clothesline as required
Wind brake prevents clothesline rotation when hanging clothes
New ergonomic height adjusting handle
25 year structural warranty*
Spare parts available

*excludes line (hank) which has a 2 year replacement warranty

Daytek® Rotary Clothesline M38

Special Order Colours

	Daytek Code	Item Number
Primrose	A02843011	0137966
White Mist	A02843030	0137965
Bark	A02841002	0137956
Light Grey	A02841007	0137962
Mercury Silver	A02841008	0137963
Sand	A02843012	0137967
Asteroid Pearl	A02841017	0137970
Timber Grey	A02841014	0137968
Black Satin	A02841015	0137958
Obsidian	A02841009	0137964
Iron Grey	A02841006	0137969
Bedrock Grey	A02841004	0137955
Coastal Blue	A02841003	0137957
Custom Made *	A02841016	0139339



*Please complete Custom Made order form at the back of this section

Product Specification

Total Line Space	38m
Maximum Line Length	2.2m
Line	3.5mm Ø 24 Nylon Strands coated with UV Stabilised PVC
Load Capacity	1kg per metre of line space
Space Between Lines	Lines 1:2 & 5:6 78mm; Lines 2:5 152mm
Height Adjustment	1,630mm minimum to 2,020mm maximum
Head Size	3.2m Ø
Space Required	4.2m Ø (with recommended clearance of 0.5m on all sides)
Lower Post	Powder Coated Galvanised Steel Tube - Ø57x1mm
Upper Post	Powder Coated Galvanised Steel Tube - Ø44.5x1mm
Arms	Powder Coated Galvanised Steel Tube - 35x19x1mm
Support Arms	Powder Coated Galvanised Steel Tube - 25x12x0.7mm
Carton Size & Weight - h x w x d / kg	2,100 x 220 x 190mm / 14.9kg